



IFP-0802 Version: 1

8-Port Fast Ethernet PoE Industrial Switch, 8 PoE Outputs, 802.3at PoE+, 200W, -40°C to 75°C

The LevelOne IFP-0802 is 10/100M industrial 8 port high power POE switch is equipped with 8 port 30Watts PSE. It is designed for 48-56VDC input sources, especially for IP surveillance, traffic monitoring and for a broad range of applications. It can be used as a stand-alone device for buses, trucks, and other vehicles for Surveillance purposes. It is being rigorously tested for your Security, Transportation and Telco application.

Key Features

- PoE ports can support the IEEE 802.3at standard and power up 30W devices
- 10/100Mbps, full/half-duplex, auto-negotiation, auto-MDI/MDIX
- -40°C to 75°C operating temperature range
- Provides DIN-rail, wall or desktop mounting
- IP30 metal case
- Redundant power inputs with Terminal Block

Specifications

System Specifications

Standards & Protocols:

IEEE 802.3 10Base-T Ethernet
IEEE 802.3u 100Base-TX Fast Ethernet
IEEE802.3x Flow Control and Back Pressure,
IEEE802.3af for POE
IEEE802.3at for POE+

Buffer Memory:

1M

Connectors and Cabling:

8 x RJ-45 10/100BaseT(X) auto negotiation,
8 x POE+ 802.3at/af PSE port
Auto MDI/MDI-X function, Full/Half duplex

Indicator:

Per Unit: Power
Per Port: Ethernet Link, PoE Status

Transmission Method:

Store & Forward

**Power Input:**

Redundant Dual DC 44V-56V Power Input
POE input 44-56VDC

Power Consumption:

5.76W@48 VDC full load, Without POE

Features**General:**

100 Base-Tx, 10Base-T Ethernet
8 Port PoE Output

PoE:

POE power per port 30watts. Maximum 36Watts
Maximum total power 200Watts with 56VDC input, Supports IEEE802.3af/at

Ease of Use:

Plug & Play

Performance**Backplane (Gbps):**

1.6G bps

MAC Address Table:

1K

Packet Forwarding Rate:

148800 bps

Environment**Power Saving:**

Green Ethernet

Acoustic Noise:

No

Temperature (°C):

-40°C ~ 75°C

Humidity (Non-condensing):

5% to 95%

Physical Specifications**Dimensions (W x D x H mm):**

142 x 105 x 36.2

Weight (g):

525

Reliability**MTBF:**

510,304 hrs (MIL-HDBK-217F) at 25°C

Approval and Compliance**EMI/EMS:**

EMI: FCC Part 15 Subpart B Class A
CE EN 55022 Class A
EMC: EN55022, EN55024

Safety:

IEC EN60950-1

Environmental Test:

EN50155/EN60068-2-6

EN50155/EN60068-2-27

EN50155/EN60068-2-32

Order Information

IFP-0802

Package Contents

IFP-0802

Power Terminal Block

Mounting Kit

User Manual

No liability or responsibility for any errors or omissions in the content.
Specifications are subject to change without notice.
All mentioned brand names are registered trademarks and property of their owners.
Copyright © Digital Data Communications GmbH, Germany. All Rights Reserved.